## → TroPly Metallic Plus - Technical Data Sheet



Physical Properties	Specifications
Substrate	ABS
Colours:	See catalogue
Gauges:	1,6 mm / 2,4 mm
Sheet Sizes:	See catalogue
Fabrication Properties:	Router, saw, die-cut and laser
UV Light Resistance:	Q Panel Accelerated Weathering Tester/UVA-340 EL Lamps > 300 hours of continuous UV/moisture exposure
Abrasion:	No visible change when tested with 0000 steel wool; Taber testing > 200 cycles with CS 17 wheel/500 grams
Cleaning Instructions:	Any cleaning material that dissolves or releases the dirt or stain from the surface can be used to clean AGM or AGG series. Household detergents such as Mr. Clean®, Windex with Ammonia D® (S.C. Johnson & Son, Inc.) or 99% isopropyl alcohol should be applied generously using a soft cloth with minimal pressure to avoid micro-scratching the soiled area. Do not use abrasives such as rubbing compounds or cleaners.
Optical:	Glossy Finish
Vicat Softening Temperature:	ASTM D-1525 212 degrees F (100 degrees C)
Specific Gravity:	ASTM D-792 1.04 g/cc
Tensile Modulus:	ASTM D-638 270,000 p.s.i.
Izod Impact Strength:	ASTM D-256 @ 73 F 3.5 ft-lbs/in
Flexural Modulus:	ASTM D-790 285,000 p.s.i.
Coefficient of Thermal Expansion:	Coefficient of Thermal Expansion
Tensile Strength @ Yield:	ASTM D-638 3,700 p.s.i.
Flexural Strength @ Yield:	ASTM D-790 7,000 p.s.i.
Heat Deflection Temperature:	ASTM D-648 (264 p.s.i. unannealed) 185degreesF(85 degrees C)
Hardness:	ASTM D-785 68 Rockwell R (L)
Flammability:	UL 94 HB 0.062 thickness

All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses, and that purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations, Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. THERE IS NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR ANY PURPOSE. PRODUCTS WILL MEET SELLER'S STANDARD SPECIFICATIONS THEREFORE, BUT THERE ARE NO OTHER WARRANTIES FOR THE PRODUCTS DESCRIBED.